

# Synthetic Fiber Rubber Gasket

Code: KXT1400



## Description

The Synthetic Fiber gasket is cut from Synthetic Fiber rubber sheets.

The Synthetic Fiber sheet is made from synthetic fiber, natural rubber, filling material and dye, compressed and calendered under high temperature and pressure into a sheet form.

Normal colour: Black with some white, blue or green-white, etc.



Item no.: KXT1400

## Synthetic Fiber Rubber Gasket

Item no.: KXT1400

- \* Synthetic Fiber gasket cut from Synthetic Fiber rubber sheet.
- \* Suitable for use as an oil-resistant jointing medium for heat installations and engine sealing.

## Typical Application

For static sealing in flange joint of pipeline, valve, shipping industry, oil, etc.

## Styles

**NCAF Gasket 1400:** cut from Synthetic Fiber rubber sheets.

Temperature: 150°C, 200°C, 250°C, 300°C, 350°C, 400°C, 450°C.

**Oil Resistant NCAF Gasket 1400OR:** cut from Oil resistant Synthetic Fiber rubber sheets.

Temperature : 150°C, 200°C, 250°C, 300°C, 350°C, 400°C, 450°C.

## Standard

ASME, JIS, JPI, ASNI, DIN, etc. Or manufactured gasket accordance customers requirements.

Copyright © 2014-2015

Ningbo Kaxite Sealing Materials Co., Ltd.

No.134,Huancheng North Road,Jiangbei District,Ningbo City,Zhejiang Province,China (Zip:315020)

Website:<http://www.seal-china.com> E-mail:[sales@seal-china.com](mailto:sales@seal-china.com),[kaxite@seal-china.com](mailto:kaxite@seal-china.com)